

KOZAK II

LIGHT ARMOURED VEHICLE



Dimensions:
7050x2500x2610



Seating capacity:
up to 11



Full weight:
15000 kg



Engine type:
Iveco, 5,9 litres turbodiesel



Main Specifications:

Base chassis	Iveco Eurocargo 4x4
Wheel arrangement	4x4
Power, h.p.	279
Torque, Nm	950
Clearance, mm	392
Turning radius, m.	8,0
Transmission	ZF, mechanical 6-speed with synchronizers
Ballistic Protection	2 (according to STANAG 4569)
Blast Protection	1a,1b (according to STANAG 4569)

- special anti-mine seats, installed back-to-back and attached to the roof turret with possibility of 7,62 PKMS and 12,7 automatic gun installation
- evacuation-and-ventilation hatches
- gun-ports in side windows landing door

- special alloyed armor steel as major protection material
- antispall layer in all side walls
- bulletproof glasses with internal antispall layer
- V-shaped hull
- multi-layer floor, absorbing blast energy

- front and rear ram bumpers
- electrical winch
- preparation for all special devices (radiostation, navigation device etc.)
- front-view camera with night vision
- rear-view camera
- parktronic intercom



- Wheels are equipped by «run-flat» that allows to move with penetrated tires
- air conditioner